ELECTRODE WELDING (MMA)

10 ▸ 130 A

Gysmi 130P

GYS
INVEST IN THE FUTURE

• Welding unit with inverter technology and microprocessor control

• The arc dynamic of the product is unique enabling the highest standard of welding result

• Can be used with all types of electrodes: rutile, basic, stainless steel & cast iron

REF.029972

Delivered in plastic box with
Earth cable (1.6m/ø16mm²)
Electrode holder (1.6m/ø16mm²)

MMA :

- ✓ Instant and easily controlled start
- ✓ Constant welding power
- ✓ Tolerant to current fluctuations or to the arc length
- ✓ High penetration and perfect arc stability

This welding unit offers the following advantages :

- ✓ **ARC FORCE** : Instantaneous increase of the current in difficult welding situation
- ✓ **HOT START** : Increased power at start
- ✓ **ANTI STICKING** : Prevents the electrode sticking

UNIT PROTECTED FOR USE ON GENERATORS AND AGAINST SUPPLY VOLTAGE VARIATIONS (+/-15%)

CE EN 60974-1

50/60Hz	AM	I2 TIG	I2 MMA	ø1,6	ø2	ø2,5	ø3,2	ø4	ø5	EN60974-1 (40°C) IA (60%)	EN60974-1 (40°C) X% (12 max)	Uo	cm kg	Protected & compatible POWER GENERATOR	
230V	13A	10A ▽ 130A	10A ▽ 130A	62	50	47	24	_	_	45A	5%	80V	11x21x25cm 2,9kg	4kW	5,0kVA